


Laminate Floor Heating Mats - ThermoLAM

for laminate floor and under-carpet heating

A young girl with dark hair, wearing a colorful striped shirt and blue jeans, is lying on her stomach on a wooden floor. She is looking down at a silver laptop computer that is open in front of her. Her hands are resting on the laptop's lid. The floor is made of light-colored wood planks. The top of the image has a red curved banner with white text.

ThermoLAM is a product specially engineered for easy installation, safety and uniform heating of laminate, engineered wood, glued hardwood and other floating floors. Its special materials ensure no 'Hot-Spots' or localized heating problems.



Construction

ThermoLam comprises of a twin conductor heating element having primary insulation of Fluoropolymer - sandwiched between two layers of specially Reinforced Aluminium Foil.

Standard Wattage : 80 W/Sq. mtr and 140 W/ Sq. mtr
 Width of Mat : 500mm
 Cold Lead : 3.0 mtr

Features

Approvals	Certified by Intertek Semko against relevant IEC / EN 60335 Standard.
User Friendly	Ease of laying - the mat can be cut & turned to fit the room.
Comfort	Ultimate Warm Experience - Uniform Heating due to Aluminium Foil and Thermostat Control.
Safety	Unique construction ensures 100% Earth Protection.
Eco-Friendly	Over 90% of ThermoLAM consists of metal, primarily Aluminium, which is now considered as a "Green-Metal". Also it does not emit any green-house gases while heating.

Product Range (140W)

Catalog No.	Length (M)	Width (M)	Area (Sq.m)	Watts (W)
LFM-T-140W/140	2	0.5	1.0	140
LFM-T-140W/210	3	0.5	1.5	210
LFM-T-140W/280	4	0.5	2.0	280
LFM-T-140W/350	5	0.5	2.5	350
LFM-T-140W/420	6	0.5	3.0	420
LFM-T-140W/490	7	0.5	3.5	490
LFM-T-140W/560	8	0.5	4.0	560
LFM-T-140W/630	9	0.5	4.5	630
LFM-T-140W/700	10	0.5	5.0	700
LFM-T-140W/840	12	0.5	6.0	840
LFM-T-140W/980	14	0.5	7.0	980
LFM-T-140W/1120	16	0.5	8.0	1120
LFM-T-140W/1260	18	0.5	9.0	1260
LFM-T-140W/1400	20	0.5	10.0	1400